

3 INCH WIDE SAFETY GREEN DETECTABLE MARKING TAPE 10 INCHES MAX. BELOW SURFACE IMPRINTED WITH

"CAUTION - BURIED SEWER

3 INCH WIDE SAFETY GREEN MARKER TAPE MAX. 18 INCH ABOVE PIPE CROWN IMPRINTED WITH "CAUTION - BURIED

SEWER PIPE BELOW"

PIPE BELOW"

SUITABLE NATIVE MATERIAL BACKFILL AS PER SPECIFICATIONS

- GROUND LINE

COMPACTED 3/4" TO NO. 4 CLEAN CRUSHED STONE (GRAD. NO. 67) FOR BEDDING AND EMBEDMENT TO MIN 4 INCHES ABOVE PIPE. SHOVEL SLICE BEDDING BENEATH THE PIPE HAUNCHES.

4 Å

TRENCH CROSS-SECTION FOR DEPTHS UP TO 16' - 0"

=|||=|||=|||=|||=|||=|||=|||=

=|||=|||=|||=|||=|||=|||=

- 1. ENGINEER OF RECORD SHALL SUBMIT LIVE AND EARTH LOADING CALCULATIONS FOR DEFLECTION AND PROJECT SPECIFIC EMBEDMENT DESIGN FOR DEPTHS
- 2. WHEN WATER TABLE CRADLE IS REQUIRED TO PREVENT SOIL MIGRATION AND/OR STABILIZE PIPE FOUNDATION SEE STANDARD DETAIL 367.
- 3. REFER TO STANDARD DETAIL 315 FOR STANDARD TRENCH WIDTH.
- 4. FOR PAVED AREAS, SEE STANDARD DETAIL 713.

BEDDING DETAIL POLYVINYL CHLORIDE FLEXIBLE SANITARY SEWER PIPE

CITY OF TULSA, OKLAHOMA ENGINEERING SERVICES DEPARTMENT

DRAWN BY: R.M.O CHECKED BY: HAJ

DATE: MARCH 2022

NOT TO SCALE

STANDARD NO.