



City of Tulsa Purchasing Department
175 E. 2nd Street 15th Floor
Tulsa, OK 74103

TAC 077i
Motor Oil, Lubricants, & Greases
Department: Asset Management
Bid Opening: November 16, 2023

Buyer: Rachel Harders
rachelharders@cityoftulsa.org
Please contact if you
have any questions

1. Delivery

You must be able to deliver the Goods and/or Services as specified in your Bid. Failure to do so may result in City Terminating your agreement or canceling the Purchase Order Pursuing collection under any performance bond, as well as seeking any other damages to which it may be entitled in law or in equity.

2. Pricing

The City of Tulsa does not guarantee any specific quantity or number of purchases that will be made during the agreement period. If the Seller's prices cannot stay competitive with the outside market, the City reserves the right to purchase from outside sources or low bidder(s).

				Safety-Kleen Systems, Inc.	
Item	Item Description	Unit of Measure	Est. Annual Usage	Unit Cost	Extended Cost
1	Motor oil, single grade, heavy duty Diesel/Gasoline. Approved for API service , CF, CF-2, and SL/SN. Minimum total base #9, with less than 1.5% sulfated ash. SAE30	12 Qt Case	8 Cases	NB	NB
2	Motor oil, multi-grade, heavy duty Diesel/Gasoline. Approved for API Service CG-4, CF-4, CF, CH-4, CI-4, SL, and SN. Minimum total base #11, with less than 1.5% sulfated ash. SAE 15W40	12 Qt Case	115	\$56.68	\$6,518.20
3	Motor oil, multi-grade, heavy duty Diesel/Gasoline. Approved for API Service CG-4, CF-4, CF, SG, CH-4, CI-4, SL, and SN. Minimum total base #11, with less than 1.5% sulfated ash. SAE 15W40	55 Gallon Drum	4	\$614.96	\$2,459.84
4	Motor oil, multi-grade light duty Diesel and Gasoline. Approved for API Service SN. API Cert. Mark ILSA GF-3(5w20, 5w30, 10w30). Must meet Ford WSS-M2C153-H. Must be energy conserving II.	12 Qt Case	40	35.20/5w20 35.40/5w30 35.57/10w30	\$1,408.00 \$1,416.00 \$1,422.80
5	Motor oil, multi-grade light duty Diesel and Gasoline. Approved for API Service SN. API Cert. Mark ILSA GF-3(5w20, 5w30, 10w30). Must meet Ford WSS-M2C153-H. Must be energy conserving II. SAE 5W20	Quarts in Bulk	5400	8.5/5w20 8.56/5w30 8.62/10w30	\$11,475.00 \$11,556.00 \$11,637.00
5A	Motor oil, multi-grade light duty Diesel and Gasoline, SAE 5W30 SN Plus API, must meet Ford Specifications WSS-M2C946-B1	Quarts in Bulk	5500	8.56/Gal	\$11,770.00
5B	Motor oil, multi-grade SAE 5W20 SN Plus API, must meet Ford Specifications WSS-M2C945-B1	12 Qt Case	75	\$35.20	\$2,640.00
6	Motor oil, multi-grade light duty Diesel and Gasoline, approved for API Service SN, SL, SN. API Cert. Mark ILSAC (5w30, 10w30). Must be energy conserving II. SAE 5W30	12 Qt Case	36	35.57/5w30 35.57/10w30	N/A \$1280.52
7	Motor oil, multi-grade light duty Diesel and Gasoline, approved for API Service SN, SL, SN. API Cert. Mark ILSAC (5w30, 10w30). Must be energy conserving II. SAE 5W30	Quarts in Bulk	2500	8.56/5w30 8.62/10w30	\$5,350.00 \$5,387.50
8	Motor oil, multi-grade light duty Diesel and Gasoline, approved for API Service SN, SL. API Cert. Mark ILSAC. Must be energy conserving II. SAE 10W30	12 Qt Case	88	\$35.57	\$3,130.16
8A	SAE 10W30 Super Duty Diesel Motor Oil, must meet Ford Specifications WSS-M2C171-F1	12 Qt Case	200	NB	NB
9	Motor oil, multi-grade light duty Diesel and Gasoline. Approved for API Service SN, SL. API Cert. Mark ILSAC (5w30, 10w30). Must be energy conserving II. SAE 10W30	55 Gallon Drum	1	\$608.24	\$608.24
10	Motor oil, multi-grade diesel. Approved for API service CK-4, with backward compatibility . Must meet chemical restrictions of less than 1.0% ash, 0.4% Sulphur, 0.12% phosphorus. SAE 15W40	1 Quart Container	1380	NB	NB
11	Motor oil, multi-grade diesel. Approved for API service CK-4, with backward compatibility. Must meet chemical restrictions of less than 1.0% ash, 0.4% Sulphur, 0.12% phosphorus. SAE 15W40	55 Gallon Drum	2	\$614.96	\$1,229.92

				Safety-Kleen Systems, Inc.	
Item	Item Description	Unit of Measure	Est. Annual Usage	Unit Cost	Extended Cost
12	Motor oil, multi-grade diesel. Approved for API service CK-4, with backward compatibility. Must meet chemical restrictions of less than 1.0% ash, 0.4% Sulphur, 0.12% phosphorus. SAE 15W40	Quarts in Bulk	37000	10.06/Gal	\$93,055.00
12A	Motor Oil, multi-grade, SAE 5W30 SN Plus API (specification) WSS-M2C946-B1	Quarts in Bulk	180	\$8.56	\$1,540.80
13	Hydraulic oil, anti-wear, ISO viscosity grade 32, rust and oxidation inhibited, minimum V.I.-102, Minimum 3680 hours on ASTM-D-943, must meet Denison HF-0, Vickers M-2950-S (5), Cincinnati Milacron P-68. Hydraulic Oil, ISO 32	5 Gallon Can	8	NB	NB
14	Hydraulic oil, anti-wear, ISO viscosity grade 32, rust and oxidation inhibited, minimum V.I.-102, Minimum 2000 hours on ASTM-D-943, must meet Denison HF-0, Vickers M-2950-S (5), Cincinnati Milacron P-68. Hydraulic Oil, ISO 32, ASTM Grade 150.	55 Gallon Drum	4	NB	NB
15	Hydraulic oil, anti-wear, ISO viscosity grade 32, rust and oxidation inhibited, minimum V.I.-102, Minimum 2000 hours on ASTM-D-943, must meet Denison HF-0, Vickers M-2950-S (5), Cincinnati Milacron P-68. Hydraulic Oil, ISO 32	Quarts in Bulk	8200	NB	NB
16	Hydraulic oil, anti-wear, ISO viscosity grade 46, Rust and oxidation inhibited, minimum V.I.-100, Must meet Denison HF-0, Vickers M-2590-S (5), Cincinnati Milacron P-70. Viscosity Index 100. Hydraulic Oil, ISO46	5 Gallon Bucket	16	NB	NB
17	Hydraulic oil, anti-wear, ISO viscosity grade 46, Rust and oxidation inhibited, minimum V.I.-100, Minimum 2000 hours on ASTM-D-943, must meet Denison HF-0, Vickers M-2590-S (5), Cincinnati Milacron P-70. Hydraulic Oil, ISO46	55 Gallon Drum	5	NB	NB
18	Hydraulic oil, anti-wear, ISO viscosity grade 68, rust and oxidation inhibited, minimum V.I.-95, Minimum 2000 hours on ASTM-D-943, must meet Denison HF-0, Vickers M-2590-S (5), Cincinnati Milacron P-69. Viscosity index 9.5, Hydraulic Oil, ISO68	5 Gallon Can	4	NB	NB
19	Hydraulic oil, anti-wear, ISO viscosity grade 68, Rust and oxidation inhibited, minimum V.I.-95, Minimum 2000 hours on ASTM-D-943, must meet Denison HF-0, Vickers M-2590-S (5), Cincinnati Milacron P-69. Hydraulic Oil, ISO68	55 Gallon Drum	2	NB	NB
20	Automatic transmission fluid. Meets latest requirements for transmissions manufactured by General Motors, Ford, Chrysler Corporation as well as requirements for Allison C-3/C-4 Torque Converters. Fluid is Dexron III, Mercon and/or Ford type H. Must meet licensing requirements and performance Requirements of: Ford Mercon, GM Dexron III, and Allison C-3/C-4. Auto. Trans. Fluid, Dexron III/Mercon/Ford Type H, and C-3/C-4	12 Qt Case	40	\$36.33	\$1,453.20
21	Automatic transmission fluid. Meets latest requirements for transmissions manufactured by General Motors, Ford, Chrysler Corporation as well as requirements for Allison C-3/C-4 Torque Converters. Fluid is Dexron III, Mercon and/or Ford type H. Must meet licensing requirements and performance Requirements of: Ford Mercon, GM Dexron III, and Allison C-3/C-4. Auto. Trans. Fluid, Dexron III/Mercon/Ford Type H, and C-3/C-4.	55 Gallon Drum	1	\$549.58	\$549.58
22	Automatic transmission fluid. Meets latest requirements for transmissions manufactured by General Motors, Ford, Chrysler Corporation as well as requirements for Allison C-3/C-4 Torque Converters. Fluid is Dexron III, Mercon and/or Ford type H. Must meet licensing requirements and performance Requirements of: Ford Mercon, GM Dexron III, and Allison C-3/C-4. Auto. Trans. Fluid, Dexron III/Mercon/Ford Type H, and C-3/C-4.	Quarts in Bulk	400	\$8.87	\$3,548.00
23	Auto. Trans. Fluid. Mercon V. Must meet licensing and performance requirements of Ford Mercon V, Mercon LV, Mercon ULV and Allison C-4.	12 Qt Case	25	NB	NB
24	Auto. Trans. Fluid. Mercon V. Must meet licensing and performance requirements of Ford Mercon V and Allison C-4.	55 Gallon Drum	1	NB	NB
25	Auto. Trans. Fluid. Mercon V. Must meet licensing and performance requirements of Ford Mercon V and Allison C-4.	Quarts in Bulk	600	NB	NB
26	Auto. Trans. Fluid. Type TES-295 Must meet Allison C-4 and ZF Transmissions-Allison TES295 specifications. MUST HAVE WRITTEN PROOF THAT USE OF PRODUCT QUOTED WILL NOT VOID MANUFACTURER'S WARRANTY.	55 Gallon Drum	10	\$1,856.25	\$18,562.50

				Safety-Kleen Systems, Inc.	
Item	Item Description	Unit of Measure	Est. Annual Usage	Unit Cost	Extended Cost
27	Tractor fluid, all purpose. Fluid shall be specially Formulated to meet service requirements for tractors of various manufactures where the use of a combination hydraulic/transmission fluid is specified. The base oil and additives shall be selected to result in a product that will comply with the following manufacturer's specifications: John Deere JDM J20C, Quatrol, Ford New Holland M2C86-B, M2C134-D, J1 Case MS1204, MS1205, MS1207, Massey Ferguson M1127A&B, M1129A, White Q-1766 GM/Allison C3/C4, Caterpillar To-2. Universal Tractor Trans./Hydraulic Fluid	5 Gallon Bucket	5	\$52.29	\$261.45
29	Kerosene – 1-K Contains 0.04 percent sulfur by weight and is designed for use in portable kerosene heaters, ASTM Standard D-3699	55 Gallon Drum	4	NB	NB
30	Multi-purpose gear lubricant. Must meet API Service Classification: GL-5 and MT-1. 80w90	Quarts in Bulk	550	12.90/Gal	\$1,773.75
30A	Multi-purpose gear lubricant. Must meet API Service Classification: GL-5 and MT-1. 80w90	5 Gallon Bucket	15	\$71.57	\$1,073.55
30B	High Temperature 4x4 front axle and wheel bearing grease WSS-M1C267-A7	Quarts	200	NB	NB
30C	SAE 80W90 Premium Rear Axle Lubricant WSP-M2C197-A	Quarts	200	NB	NB
31	Multi-purpose gear lubricant. Must meet API Service Classification: GL-5 and MT-1. 85w140	5 Gallon Bucket	2	\$74.35	\$148.70
32	Multi-purpose gear lubricant. Must meet API Service Classification: GL-5 and MT-1. 85w140	64 Quart Drum	2	NB	NB
33	Synthetic Gear Oil. ISO VG 220. High Temperature thermal/oxidation resistance. High viscosity Index and absence of wax. Certified GC-LB	5 Gallon Pail	10	NB	NB
34	Grease. Multi-purpose, wheel bearing. NLGI #2 Timken OK load, ASTM D 2509, lb. – 55. Temp. Range 0 to 250-degree F.	14 oz Tubes	1000	46.29/10 Tubes	\$4,629.00
35	Grease. Multi-purpose, wheel bearing. NLGI consistency #2 Timken OK load, ASTM D 2509, lb. – 55. Temp. Range 0 to 250-degree F.	5 Gallon Bucket	1	\$152.48	\$152.48
36	Antifreeze, Glycol, Low Silicate, must be 100% concentrate. Must meet or exceed all ASTM & SAE Standards.	1 Gallon Jug	1026	NB	NB
37	Antifreeze, Glycol, Low Silicate, must be 100% concentrate. Must meet or exceed all ASTM & SAE Standards.	55 Gallon Drum	5	\$622.51	\$3,112.55
37A	Antifreeze, Glycol, Low Silicate, Ready to use. Must meet or exceed all ASTM & SAE Standards	1 Gallon Jug	500	NB	NB
38	Antifreeze, Glycol, Low Silicate, must be 100% concentrate. Must meet or exceed all ASTM & SAE Standards.	Quarts in Bulk	1100	NB	NB
39	Antifreeze, Extended life, must meet performance specs for: ASTM D-3306, ASTM D-4340, GM 1825M, GM6277M, Chrysler MS7170, FORD WSS-M97B44-D, and SAE J1034.	1 Gallon Jug	36	NB	NB
40	Aerial Hydraulic Fluid. All weather, multi-viscosity, anti-wear. Designed for use in aerial buckets, mobile hydraulic systems, etc. A fluid with dielectric (insulating) properties is required. Foam resistant and oxidation inhibited. Must meet ASTM D877, at 25KV or better. Min. VI of 140.	5 Gallon Can	4	NB	NB
TOTAL COST NOT TO EXTENDED: (All costs must be included or your bid will be disqualified)				\$158,216.92	
Delivery				3-5 Days	
Annual Price Adjustment				5%	

THE CITY DOES NOT GUARANTEE ANY SPECIFIC QUANTITY OR NUMBER OF PURCHASES, IF ANY, THAT WILL BE MADE DURING THE AGREEMENT TERM.